

| | |
|-------------------------------|---------------------------|
| Product Name: | Bluelab PeriPod M3 |
| Product Code: | PERIPODM3 |
| UPC Code: | 9421024920876 |
| Country of Origin: | New Zealand |
| Tariff Code: | 9027.80 |
| Shipping Quantity: | Sold as singular unit |
| Packaging Information: | |
| Packaged Weight: | 1.7 kg / 3.75 lb |
| Packaged Length: | 335 mm / 13.19 in |
| Packaged Width: | 215 mm / 8.465 in |
| Packaged Height: | 170 mm / 6.693 in |

Sales Description:

NOTE: this copy can be used in brochures, catalogues or online

Confidently automate the perfect pH and nutrient levels in nutrient reservoirs

Easy integration for nutrient solution management.

Your time is extremely valuable, don't waste it manually dosing. Designed to be teamed with the Bluelab® Pro Controller for a fully integrated solution for optimal reservoir dosing, the Bluelab® PeriPod™ is a simple and reliable inclusion.

The Bluelab® PeriPod™ responds to dosing triggers received from the Bluelab® Pro Controller and pumps pH adjusters and nutrient stock solutions into your reservoir using peristaltic pumps. Accurately measure, control and maintain pH levels. Grow sites are all different so now you can choose the size to match your set up needs and add optional extras, external alarm box and sample pot, to your nutrient dosing system set up.

Visit the Bluelab® PeriPod™ pages on bluelab.com to read more about which pump size is suitable for your system.

Features:

M Versions:

- 1x 120ml (4fl oz)/min peristaltic pump for dosing pH adjuster solutions
- 2x 120ml (4fl oz)/min peristaltic pumps for dosing nutrient stock solutions
- Rugged wall mount design
- Individual pump priming and calibration
- Replaceable peristaltic pumps and tubing
- Compatible with Bluelab® Pro Controller™ and most Bluelab® DoseTronic™ models

Length: 288 mm / 11.3 in
Height: 112 mm / 4.4 in

Product Guarantee:

Two year limited guarantee, proof of purchase required. Six months for pumps & tubing



Product Image:



Product images available for Screen or Web use:

- Bluelab-PeriPod-M3-Front-Web
- Bluelab-PeriPod-M3-Front-Web-sml
- Bluelab-PeriPod-M3-Hero-WEB
- Bluelab-PeriPod-M3-Hero-WEB-sml

Product images available for PRINT:
Note: these images are high resolution in CMYK.

- Bluelab-PeriPod-M3-Hero-flat-MR-cmyk
- Bluelab-PeriPod-M3-Front-MR-flat-cmyk

Technical Specifications:

| | |
|--|----------------------------------|
| Pump Function: | #1: pH, #2: EC A, #3: EC B |
| Pump Flow Rate per Minute: | 120 ml 4 fl oz |
| Solution Temperature: | 5 - 50°C, 41 - 122°F |
| Environment Temperature: | 5 - 40°C / 41 - 104°F |
| Flow Rate Accuracy at 25°C or 77°F: | ±10% |

{This Product Information Sheet is NOT intended for distribution to end users.}